

## MAGIC VELVET DELUXE P301



Composition

Weight

VVIGLI

Туре

77



WATER REPELLENT



PETPROOF



NON-FLAMMABLE





100% PES

 $880 \text{ g/m}^2 \pm 5\%$ 

142 ± 2 cm

knitted fabric

upholstery fabric

4		P		
L	1	3	Δ	
1	4	<b>″</b> ,	7	

Abrasion resistance PN-EN ISO 12947-2:2017-02



Fuzzing and pilling PN-EN ISO 12945-2:2002



Seam slippage PN-EN ISO 13936-2:2005



Wet rubbing PN-EN ISO 105-X12:2016-08



Dry rubbing PN-EN ISO 105-X12:2016-08



Cigarette test
PN-EN 1021-1:2014-12

**60 000** rubs

3 | warp

5

3 | weft

4

4

Α

Α

А

А

В

✓

Maintenance















- The level of Cleanaboo and Cleanaboo+ protection can decrease after each cleaning
  of the fabric, but the process does not affect the look.
- 2. Respective fabric batches may differ slightly in shade from the colours presented in the sampler.
- 3. Toptextil Sp. z o.o. is not liable for mechanical damage and such as may be attributable to the improper use and/or cleaning of the fabric.
- Bobbling and pilling are caused by the properties of the fabric and impossible to avoid entirely. This is a natural process, which occurs as the fabric is used.
- Due to friction against the fabric, colourants can migrate from darker to brighter fabrics.
- 6. Long-term exposure to sunlight can cause discolouration.
- According to ISO 13936, the proper thickness of the bead is 33-35 of the stitching per 10 cm of the fabric with the minimum distance of the stitching from the edge of the fabric of at least 1.5 cm.
- It is assumed that depending on the type of fabric, resistance to abrasion within the scope of 2,000-4,000 Martindale cycles corresponds with the period of 1 year of the proper use of the fabric.